

SIDEWALK

NEW JERSEY OF NEWARK

TO METER 1" -2" COPPER \forall TUBING OR LESS (TYPE "K") CORPORATION TAP - 1" (1 OR 11 NEWARK STANDARD CURB STOP CONCRETE UNDER CURB STOP TO PROFILE VIEW FIRM GROUND N.T.S. CURB -TO METER

MIN

CURB LINE -

NEWARK STANDARD

CURB STOP

VALVE BOX OR

CURB BOX

F.G.

4' MINIMUM COVER

PLAN VIEW N.T.S.

O'CLOCK POSITION)

- BLOCK UNDER

CORPORATION TAP - 1"

LOOP

EXISTING

WATER

MAIN

NOTES:

EXPANSION LOOP

REQUIRED NEAR

MAIN

1. 1"-2" TYPE "K" COPPER TUBING ONLY. ALL FITTINGS TO BE FLARED. NO SOLDIER JOINTS ALLOWED UNDERGROUND. CURB BOX REQUIRED FOR 1"SERVICE. CORPORATION TO BE TAPPED ON UPPER QUARTER OF PIPE.

1" -2" COPPER TUBING OR LESS (TYPE "K")

- 2. NOTICE SHALL BE GIVEN TO THE WATER DEPARTMENT PRIOR TO CONSTRUCTION
- 3. FOR SERVICES LARGER THAN 2" TEE CONNECTION WITH DIP SERVICE LATERAL (NO COPPER TUBING)